



Dot-peen marking integration unit EasyMarker++

Integration into manufacturing lines – flexible and individual marking.

Dot-peen marking integration unit EasyMarker++

Integration into manufacturing lines – flexible and individual marking.



WIR. PRÄGEN. ZUKUNFT.

Benefits

- For changing markings as well as DataMatrix-Code
- Very flexible due to adjustable font size and with as well as marking depth
- Mark up to 7 characters/sec.
- Maximum flexibility through integration in any chosen position
- Marking area max. 80 x 80 mm
- Pneumatic version (option: electrical version)

Control

- PC (USB)
- Controller, PCA-control (option)
- Serial interface, E/As, Profibus (option)

Technical data

		EasyMarker++	Blue Cube	PM Micro A
Connection (electrical/pneum.)		240 V / 6 bar	115 - 240 V / 6 bar	240 V / 6 bar
Max. power of impact	N	100	300	300
Max. impact stroke	mm	5	5	5
Max. marking speed	mm/s	100	150	350
Max. marking speed	Characters/sec.	7	6	7
Dimensions (Standard)	mm	280 x 233 x 240	131 x 84,4 x 300	Depends on version
Weight (Standard)	kg	ca. 10	ca. 3	ab 7
Marking area				
Version 1 mit cover / rear side	mm	60 x 70	60 x 30	60 x 40
Version 2 without cover / Standard	mm	80 x 80	-	100 x 50
Version 3	mm	-	-	200 x 80
Version 4	mm	-	-	200 x 200

Dot-peen marking integration unit EasyMarker++

Integration into manufacturing lines – flexible and individual marking.



WIR. PRÄGEN. ZUKUNFT.

Accessories



Cover



Touch-Display TC 100

Please contact us

We are pleased to make a **marking sample** as well as a **non-binding offer**.
You are welcome to contact us by phone, mail or fax.



+49 (0)7141 / 374567



info@lb-pt.de



+49 (0)7141 / 31386